







BRASS FINserts FOR PLASTIC & WOOD



Fininserts provide strong metal threads in wood, composition board and thermoplastics such as nylon, polystyrene, cellulose acetate and cyclocac. By distributing stress over a greater surface area, firm permanent fastening is ensured. The fins give higher holding strength in softer materials. Available with one, two or three fins for varying material thickness, Fininserts prevent splintering, splitting and thread pullout.



170 SERIES

170-006, 170-008, 170-332

270 SERIES

270-006, 270-008, 270-332, 270-3, 270-4

370 SERIES

370-332, 370-4, 370-5

Thread Size	Dash Number	A	B	C	Starting Hole Size	A	B	C	Starting Hole Size	A	B	C	Starting Hole Size
6-32	—006	.210	.237	.189	.205 (#5)	.210	.237	.189	.205 (#5)	—	—	—	—
8-32	—008	.236	.263	.215	.234 (15/64)	.236	.263	.215	.234 (15/64)	—	—	—	—
10-32	—332	.263	.290	.242	.261 (G)	.263	.290	.242	.261 (G)	.347	.368	.318	.344 (11/32)
10-24	—3	—	—	—	—	.263	.290	.242	.261 (G)	—	—	—	—
1/4-20	—4	—	—	—	—	.330	.357	.309	.328 (21/64)	.409	.431	.381	.406 (13/32)
5/16-18	—5	—	—	—	—	—	—	—	—	.471	.493	.443	.469 (15/32)



240 E. Rosecrans Ave. • Gardena, CA 90248
(800) 234-5613 • Fax (310) 868-2905
www.ezlok.com • sales@ezlok.com